


Stainless Steel Housing Ideal for Food Industry PAT Pending



- Strong resistance against detergents, disinfectants, and jet liquid flow.
- Product lineup includes BGS Reflective Models and Through-beam Models with built-in slits.
- Certified by Ecolab Europe.



Be sure to read *Safety Precautions* on page 13.

For the most recent information on models that have been certified for safety standards, refer to your OMRON website.

Features



Withstands Detergent and Disinfectant Spray


We used SUS316L for the case and the best material for all parts to achieve **200 times the durability of the E3Z** (in 1.5% solution of sodium hydroxide at 70°C) to make the E3ZM suitable for the cleaning conditions of food-processing machinery.



Superior Protective Structure


The first IP69K* (DIN 40050-9) protective structure in the world for a square metal photoelectric sensor. Suitable for high-temperature, high-pressure jet water spray cleaning applications.

* Refer to the footnote on page 5 (ratings and specifications table).




Shape and Markings Designed for Greater Hygiene

Few indentations in the shape means less dust and water can collect, making the E3ZM more hygienic. No labels have been used in order to prevent foreign matter contaminating food products. The E3ZM model and lot numbers are imprinted using a laser marker.



Rear

Structural Design That Provides Excellent Environment-resistance*




*Do not use the E3ZM in an oily environment.

Unique Members of the E3ZM Family

BGS Reflective Models

E3ZM-LS6□H/LS8□H

Three models with different fixed sensitivity (rated sensing distances) have been created. These models cover the sensing ranges of the E3Z-LS61.





Through-beam Inner Aperture Models

E3ZM-T63

Fine beam without attaching an external aperture. This eliminates malfunctions from residual water drops, even immediately after washing.

A Better Fit for the Application





The E3ZM can be used in those harsh cleaning environments in which the E3Z was difficult to use. E3ZM passed the material resistance tests and is certified by Ecolab.



Ordering Information

Sensors (Refer to Dimensions on page 15.)

 Red light  Infrared light

| Sensing method | Appearance | Connection method | Sensing distance | | Model | |
|------------------------------------|---|------------------------|---------------------------------|------|--|--|
| | | | | | NPN output | PNP output |
| Through-beam (Emitter + Receiver) |  | Pre-wired (2 m) | | 15 m | E3ZM-T61 2M Emitter E3ZM-T61-L 2M Receiver E3ZM-T61-D 2M | E3ZM-T81 2M Emitter E3ZM-T81-L 2M Receiver E3ZM-T81-D 2M |
| | | Connector (M8, 4 pins) | | | E3ZM-T66 | E3ZM-T86 Emitter E3ZM-T86-L Receiver E3ZM-T86-D |
| | | Pre-wired (2 m) | 0.8 m | | E3ZM-T63 2M Emitter E3ZM-T63-L 2M Receiver E3ZM-T63-D 2M | E3ZM-T83 2M Emitter E3ZM-T83-L 2M Receiver E3ZM-T83-D 2M |
| | | Connector (M8, 4 pins) | (apertures built in) | | E3ZM-T68 | E3ZM-T88 Emitter E3ZM-T88-L Receiver E3ZM-T88-D |
| Retro-reflective with MSR function |  *1 | Pre-wired (2 m) | | *2 | E3ZM-R61 2M | E3ZM-R81 2M |
| | | Connector (M8, 4 pins) | 4 m (100 mm) (Using E39-R1S) | | E3ZM-R66 | E3ZM-R86 |
| Diffuse-reflective |  | Pre-wired (2 m) | 1 m | | E3ZM-D62 2M | E3ZM-D82 2M |
| | | Connector (M8, 4 pins) | | | E3ZM-D67 | E3ZM-D87 |
| BGS reflective (fixed distance) |  | Pre-wired (2 m) | 10 to 100 mm | | E3ZM-LS61H 2M | E3ZM-LS81H 2M |
| | | Connector (M8, 4 pins) | | | E3ZM-LS66H | E3ZM-LS86H |
| | | Pre-wired (2 m) | 10 to 150 mm | | E3ZM-LS62H 2M | E3ZM-LS82H 2M |
| | | Connector (M8, 4 pins) | | | E3ZM-LS67H | E3ZM-LS87H |
| | | Pre-wired (2 m) | 10 to 200 mm | | E3ZM-LS64H 2M | E3ZM-LS84H 2M |
| | | Connector (M8, 4 pins) | | | E3ZM-LS69H | E3ZM-LS89H |

*1. The Reflector is sold separately. Select the Reflector model most suited to the application.

*2. Values in parentheses indicate the minimum required distance between the Sensor and Reflector.

Accessories (Order Separately)

Reflectors (A Reflector is required for each Retro-reflective Sensor: A Reflector is not provided with the Sensor. Be sure to order a Reflector.)
(Refer to Dimensions on E39-L/E39-S/E39-R.)

| Name | E3ZM-R Sensing distance * | | Model | Quantity | Remarks |
|------------------------|---------------------------|-----------------|---------|----------|---|
| | Rated value | Reference value | | | |
| Reflector | 3 m (100 mm) | — | E39-R1 | 1 | <ul style="list-style-type: none"> Reflectors are not provided with Retro-reflective models. The MSR function is enabled. |
| | 4 m (100 mm) | — | E39-R1S | 1 | |
| | — | 5 m (100 mm) | E39-R2 | 1 | |
| | — | 2.5 m (100 mm) | E39-R9 | 1 | |
| | — | 3.5 m (100 mm) | E39-R10 | 1 | |
| Fog Preventive Coating | — | 3 m (100 mm) | E39-R1K | 1 | <ul style="list-style-type: none"> Reflectors are not provided with Retro-reflective models. The MSR function is enabled. |
| Small Reflector | — | 1.5 m (50 mm) | E39-R3 | 1 | |
| Tape Reflector | — | 700 mm (150 mm) | E39-RS1 | 1 | |
| | — | 1.1 m (150 mm) | E39-RS2 | 1 | |
| | — | 1.4 m (150 mm) | E39-RS3 | 1 | |

Note: If you use the Reflector at any distance other than the rated distance, make sure that the stability indicator lights properly when you install the Sensor.

* Values in parentheses indicate the minimum required distance between the Sensor and Reflector.

Mounting Brackets A Mounting Bracket is not enclosed with the Sensor. Order a Mounting Bracket separately if required.
(Refer to Dimensions on E39-L/F39-L/E39-S/E39-R.)

| Appearance | Model (Material) | Quantity | Remarks | Appearance | Model (Material) | Quantity | Remarks |
|------------|-------------------------|----------|-------------------------------------|------------|-------------------------|----------|--|
| *1 | E39-L153 (SUS304) *1 | 1 | Mounting Brackets | *2 | E39-L98 (SUS304) *2 | 1 | Metal Protective Cover Bracket |
| *1 | E39-L104 (SUS304) *1 | 1 | | *2 | E39-L150 (SUS304) *2 | 1 set | (Sensor adjuster) |
| *2 | E39-L43 (SUS304) *2 | 1 | Horizontal Mounting Bracket | *2 | E39-L151 (SUS304) *2 | 1 set | Easily mounted to the aluminum frame rails of conveyors and easily adjusted. |
| *2 | E39-L142 (SUS304) *2 | 1 | Horizontal Protective Cover Bracket | *2 | E39-L144 (SUS304) *2 | 1 | For left to right adjustment |
| *2 | E39-L44 (SUS304) *2 | 1 | Rear Mounting Bracket | *2 | E39-L144 (SUS304) *2 | 1 | Compact Protective Cover Bracket |

Note: When using a Through-beam Sensor, order one Mounting Bracket for the Receiver and one for the Emitter.

*1. Cannot be used for Standard Connector models with mounting surface on the bottom. In that case, use Pre-wired Connector models.

*2. Cannot be used for Standard Connector models.

Sensor I/O Connectors (Sockets on One Cable End)

(Models for Connectors: A Connector is not provided with the Sensor. Be sure to order a Connector separately.)

(Refer to Dimensions on XS3.)

| Size | Cable | Appearance | Cable type | | Model |
|----------------|----------|----------------|------------|--------|-----------------|
| M8 (4 pins) *1 | Standard | Straight *2 | 2 m | 4-wire | XS3F-E421-402-A |
| | | | 5 m | | XS3F-E421-405-A |
| | | L-shaped *2 *3 | 2 m | | XS3F-E422-402-A |
| | | | 5 m | | XS3F-E422-405-A |

Note: When using a Through-beam Sensor, order one Mounting Bracket for the Receiver and one for the Emitter.

*1. Cable specifications: Outer coating material: PVC, Nut material: Stainless steel, Degree of protection: IP67 (IEC 60529)

*2. The connector will not rotate after connecting.

*3. The cable is fixed at an angle of 180° from the sensor emitter/receiver surface.

Ratings and Specifications

| Sensing method | | Through-beam | | Retro-reflective with MSR function | Diffuse-reflective Models |
|---|--|---|------------------------|---|--------------------------------------|
| Model | NPN output | E3ZM-T61 E3ZM-T66 | E3ZM-T63 E3ZM-T68 | E3ZM-R61 E3ZM-R66 | E3ZM-D62 E3ZM-D67 |
| Item | PNP output | E3ZM-T81 E3ZM-T86 | E3ZM-T83 E3ZM-T88 | E3ZM-R81 E3ZM-R86 | E3ZM-D82 E3ZM-D87 |
| Sensing distance | | 15 m | 0.8 m | 4 m [100 mm] (Using E39-R1S) 3 m [100 mm] (Using E39-R1) | 1 m (White paper 300 × 300 mm) |
| Spot diameter (typical) | | — | | — | |
| Standard sensing object | | Opaque: 12-mm dia. min. | Opaque: 2-mm dia. min. | Opaque: 75-mm dia. min. | — |
| Differential travel | | — | | 20% of sensing distance max. | |
| Black/white error | | — | | — | |
| Directional angle | | Emitter, Receiver: 3° to 15° | | Sensor: 3° to 10° Reflector: 30° | — |
| Light source (wavelength) | | Infrared LED (870 nm) | | Red LED (660 nm) | Infrared LED (870 nm) |
| Power supply voltage | | 10 to 30 VDC, including 10% ripple (p-p) | | — | |
| Current consumption | | 40 mA max. (Emitter 20 mA max., Receiver 20 mA max.) | 25 mA max. | | |
| Control output | | Load power supply voltage: 30 VDC max., Load current: 100 mA max. (Residual voltage: 2 V max.) Open-collector output (NPN/PNP output depending on model) Light-ON/Dark-ON switch selectable | | — | |
| Protection circuits | | Reversed power supply polarity protection, Output short-circuit protection, and Reversed output polarity protection | | Reversed power supply polarity protection, Output short-circuit protection, Mutual interference prevention, and Reversed output polarity protection | |
| Response time | | Operate or reset: 1 ms max. | | — | |
| Sensitivity adjustment | | One-turn adjuster | | — | |
| Ambient illumination (Receiver side) | | Incandescent lamp: 3,000 lx max., Sunlight: 10,000 lx max. | | — | |
| Ambient temperature range | | Operating: -25 to 55°C, Storage: -40 to 70°C (with no icing or condensation) | | — | |
| Ambient humidity range | | Operating: 35% to 85%, Storage: 35% to 95% (with no condensation) | | — | |
| Insulation resistance | | 20 MΩ min. at 500 VDC | | — | |
| Dielectric strength | | 1,000 VAC, 50/60 Hz for 1 min | | — | |
| Vibration resistance | | Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions | | — | |
| Shock resistance | | Destruction: 500 m/s ² 3 times each in X, Y, and Z directions | | — | |
| Degree of protection * | | IEC: IP67, DIN 40050-9: IP69K | | — | |
| Connection method | | Pre-wired cable (standard length: 2 m) M8 4-pin Connector | | — | |
| Indicator | | Operation indicator (yellow), Stability indicator (green) (Emitter has only power supply indicator (green).) | | — | |
| Weight (packed state) | Pre-wired models (with 2-m cable) | Approx. 150 g | | Approx. 90 g | |
| | Connector models | Approx. 60 g | | Approx. 40 g | |
| Materials | Case | SUS316L | | — | |
| | Lens | PMMA (polymethylmethacrylate) | | — | |
| | Display | PEI (Polyetherimide) | | — | |
| | Sensitivity adjustment and mode selector switch | PEEK (polyetheretherketone) | | — | |
| | Seals | Fluoro rubber | | — | |
| Accessories | | Instruction sheet (Note: Reflectors and Mounting Brackets are sold separately.) | | — | |

* IP69K Degree of Protection Specifications

IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.

The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.

The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



| Sensing method | | BGS Reflective Models | | |
|---|---|--|--|--------------------------|
| Model | NPN output | E3ZM-LS61H E3ZM-LS66H | E3ZM-LS62H E3ZM-LS67H | E3ZM-LS64H E3ZM-LS69H |
| Item | PNP output | E3ZM-LS81H E3ZM-LS86H | E3ZM-LS82H E3ZM-LS87H | E3ZM-LS84H E3ZM-LS89H |
| Sensing distance | 10 to 100 mm (White paper 100 × 100 mm) | 10 to 150 mm (White paper 100 × 100 mm) | 10 to 200 mm (White paper 100 × 100 mm) | |
| Spot diameter (typical) | 4-mm dia. at sensing distance of 100 mm | 12-mm dia. at sensing distance of 150 mm | 18-mm dia. at sensing distance of 200 mm | |
| Standard sensing object | | — | | |
| Differential travel | 3% of sensing distance max. | 15% of sensing distance max. | 20% of sensing distance max. | |
| Black/white error | 5% of sensing distance max. | 10% of sensing distance max. | 20% of sensing distance max. | |
| Directional angle | | — | | |
| Light source (wavelength) | Red LED (650 nm) | Red LED (660 nm) | | |
| Power supply voltage | 10 to 30 VDC, including 10% ripple (p-p) | | | |
| Current consumption | 25 mA max. | | | |
| Control output | Load power supply voltage: 30 VDC max., Load current: 100 mA max. (Residual voltage: 2 V max.) Open-collector output (NPN/PNP output depending on model) Light-ON/Dark-ON cable connection selectable | | | |
| Protection circuits | Reversed power supply polarity protection, Output short-circuit protection, Reversed output polarity protection, Mutual interference protection | | | |
| Response time | Operate or reset: 1 ms max. | | | |
| Sensitivity adjustment | — | | | |
| Ambient illumination (Receiver side) | Incandescent lamp: 3,000 lx max., Sunlight: 10,000 lx max. | | | |
| Ambient temperature range | Operating: -25 to 55°C, Storage: -40 to 70°C (with no icing or condensation) | | | |
| Ambient humidity range | Operating: 35% to 85%, Storage: 35% to 95% (with no condensation) | | | |
| Insulation resistance | 20 MΩ min. at 500 VDC | | | |
| Dielectric strength | 1,000 VAC, 50/60 Hz for 1 min | | | |
| Vibration resistance | Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions | | | |
| Shock resistance | Destruction: 500 m/s ² 3 times each in X, Y, and Z directions | | | |
| Degree of protection * | IEC: IP67, DIN 40050-9: IP69K | | | |
| Connection method | Pre-wired cable (standard length: 2 m) M8 4-pin Connector | | | |
| Indicator | Operation indicator (yellow), Stability indicator (green) | | | |
| Weight (packed state) | Pre-wired models (with 2-m cable) | Approx. 90 g | | |
| | Connector models | Approx. 40 g | | |
| Materials | Case | SUS316L | | |
| | Lens | PMMA (polymethylmethacrylate) | | |
| | Display | PEI (Polyetherimide) | | |
| | Seals | Fluoro rubber | | |
| Accessories | Instruction sheet (Note: Mounting Brackets are sold separately.) | | | |

* IP69K Degree of Protection Specifications

IP69K is a protection specification stipulated by DIN 40050 Part 9 of the German standards.

The test item is sprayed with 80°C water from a nozzle of a specified shape at a water pressure of 80 to 100 bar. The amount of water is 14 to 16 liters per minute.

The distance between the test item and the nozzle is 10 to 15 cm. The water is discharged at angles of 0°, 30°, 60°, and 90° from the horizontal plane for 30 seconds at each angle while the test item is rotated horizontally.



Dimensions

Sensors

Through-beam Models*

Pre-wired Models

E3ZM-T61


E3ZM-T81

E3ZM-T63


E3ZM-T83



Emitter



Receiver



Through-beam Models*

Standard Connector

E3ZM-T66


E3ZM-T86

E3ZM-T68

E3ZM-T88




Emitter



| Terminal No. | Specifications |
|--------------|----------------|
| 1 | +V |
| 2 | --- |
| 3 | 0 V |
| 4 | --- |

Receiver



| Terminal No. | Specifications |
|--------------|----------------|
| 1 | +V |
| 2 | --- |
| 3 | 0 V |
| 4 | Output |

* Models numbers for Through-beam Sensors (E3ZM-T□□) are for sets that include both the Emitter and Receiver.

The model number of the Emitter is expressed by adding "L" to the set model number (example: E3ZM-T61-L 2M), the model number of the Receiver, by adding "-D" (example: E3ZM-T61-D 2M.) Refer to Ordering Information to confirm model numbers for Emitter and Receivers.

Retro-reflective Models**Pre-wired Models**

E3ZM-R61

E3ZM-R81

Diffuse-reflective Models**Standard Connector**

E3ZM-D62

E3ZM-D82

BGS Reflective Models**Pre-wired Models**

E3ZM-LS61H


E3ZM-LS62H

E3ZM-LS64H


E3ZM-LS81H

E3ZM-LS82H

E3ZM-LS84H




*No sensitivity adjuster and operation selector with BGS reflective model


**Retro-reflective Models****Standard Connector**

E3ZM-R66

E3ZM-R86



*No sensitivity adjuster and operation selector with BGS reflective model



| Terminal No. | Specifications |
|--------------|----------------|
| 1 | +V |
| 2 | — |
| 3 | 0 V |
| 4 | Output |

Diffuse-reflective Models**Standard Connector**

E3ZM-D67

E3ZM-D87

BGS Reflective Models**Standard Connector**

E3ZM-LS66H

E3ZM-LS67H

E3ZM-LS69H

E3ZM-LS86H

E3ZM-LS87H

E3ZM-LS89H